

# DH-PFS3005-5ET-L

## 5-Port Desktop Fast Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7×24H: Stable performance for long-term operation

### System Overview

5 × 10/100 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

### Technical Specification

#### Performance

Layer	Layer 2
Managed	No

#### Hardware

Standard Power Supply	Yes
PoE	No
Ethernet Port	5
Ethernet Port Rate	100 Mbps
Power Supply	5V/500mA DC
Operating Temperature	-10°C to 55°C (14°F to 131°F)
Operating Humidity	10%–90%
Storage Temperature	-20°C to 70°C (-4°F to 158°F)
Storage Humidity	10%–90%
Power Consumption	Idling: 0.65W Full load: 1.3W

#### Performance

Switching Capacity	1 Gbps
Packet Forwarding Rate	0.744 Mpps
Packet Buffer Memory	448 Kbits
MAC Table Size	1K
Standards Compliance	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE802.3az

### Application

The product is applicable to small and medium office and home networks.

### General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.04 kg (0.09 lb)
Gross Weight	0.14 kg (0.31 lb)
Dimensions	77 mm × 46 mm × 21 mm (3.03" × 1.81" × 0.83")
Packaging Dimensions	94 mm × 55 mm × 107 mm (3.70" × 2.17" × 4.21")

### Dimensions (mm[inch])

