

# EXPLOSION - PROOF PRODUCTS



ATEX & IECEx



304/316L Stainless Steel




Starlight

# Explosion - proof Products

## Explosion - proof Cameras

Model	DH-EPC230U	DH-EPC230U-PTZ	DH-EPC245U-PTZ	DH-EPC230U-PTZ-IR	DH-EPC245U-PTZ-IR
					
Image Sensor	1/2.8" STARVIS™ CMOS	1/2.8" STARVIS™ CMOS		1/2.8" STARVIS™ CMOS	
Backlight Compensation	BLC / HLC / WDR(120dB)	BLC / HLC / WDR(120dB)		BLC / HLC / WDR(120dB)	
Min. Illumination	Color: 0.005Lux@F1.6; 0Lux@F1.6(IR On)	Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6		Color: 0.005Lux@F1.6; B/W: 0.0005Lux@F1.6	
Max. IR Distance	100m(328ft)	--		100m (328ft)	200m (656ft)
Focal Length	4.5mm~135mm	4.5mm~135mm	3.95mm~177.7mm	4.5mm~135mm	3.95mm~177.7mm
Preset Speed	--	Pan: 40° /s; Tilt: 40° /s		Pan: 40° /s; Tilt: 40° /s	
Compression	H.265 / H.264 / MJPEG	H.265 / H.264 / MJPEG		H.265 / H.264 / MJPEG	
Interoperability	ONVIF, CGI	ONVIF, CGI		ONVIF, CGI	
Resolution	1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1(704×576/704×480)/ CIF(352×288/352×240)	1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1(704×576/704×480)/ CIF(352×288/352×240)		1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1(704×576/704×480)/ CIF(352×288/352×240)	
IVS	Tripwire, Intrusion, Missing/Abandoned, Face Detection	--	Tripwire, Intrusion, Missing/Abandoned, Face Detection	--	Tripwire, Intrusion, Missing/Abandoned, Face Detection
Memory Slot	Micro SD card, Max 256GB	Micro SD card, Max 256GB		Micro SD card, Max 256GB	
Alarm	2/1 channel In/Out	2/1 channel In/Out		2/1 channel In/Out	
Power Supply	AC220V(AC100V ~ 240V)	AC220V(AC100V ~ 240V)		AC220V(AC100V ~ 240V)	
Power Consumption	10W, 25W(IR On)	35W, 60W(Heater on)		40W, 75W (IR on, Heater On)	
Working Temperature	-40°C ~ 60°C	-40°C ~ 60°C		-40°C ~ 60°C	
Ingress Protection	IP68	IP68		IP68	
Material	304 Stainless Steel	316L Stainless Steel		316L Stainless Steel	

## Explosion-proof Accessories

Model	DH-ZAJ300	DH-ZA-JXD4	DH-GE1500
			
Material	316L Stainless Steel	316L Stainless Steel	316L Stainless Steel
Product Dimension	347mm(L) x 177mm(H)	187mm(L) x 84mm(H)	1.5m(L)
Inside Dimension	234mm(L) x 234mm(W) x 119mm(H)	100mm(L) x 100mm(W) x 75mm(H)	--
Ingress Protection	IP68	IP68	IP68
Working Temperature	-40°C ~ 60°C, ≤95% RH	-40°C ~ 60°C, ≤95% RH	-40°C ~ 60°C, ≤95% RH
Weight	14.7Kg	3.2Kg	1.5Kg

\* Design and specifications are subject to change without notice.

Ver. 1, Sep. 2019

## DAHUA TECHNOLOGY

No.1199 Bin'an Road, Binjiang District, Hangzhou, China. 310053

Tel: +86-571-87688883 Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuasecurity.com

